

 PHÓS
LIGHTING SOLUTIONS



LT 8500 MH

LT 8500 HA

LT 8500S HA

LT 8500 LED

LT 5500 HA

LT 7000 LED
ATEX

Engine

Make model & rpm	Kubota D1105 3 cyl - 1500rpm	Kubota D1105 3 cyl - 1500rpm	Kubota D1105 3 cyl - 1500rpm	Kubota Z482 2 cyl - 1500rpm	Yanmar L48 1 cyl - 3000rpm	N.A.
Fuel tank capacity	80 litres	80 litres	80 litres	80 litres	3,6 litres	N.A.
Fuel consumption	1,85 litres per hour	1,85 litres per hour	2 litres per hour	0,55 litres per hour	0,4 litres per hour	N.A.
Run time before refuelling	43 hours	43 hours	40 hours	145 hours	9 hours	N.A.
Auxiliary outlet	3 kVA	3 kVA	1,5 kVA	1 kVA	-	16A@230V

Mast Height

8,5 m	8,5 m	8,5 m	8,5 m	8,5 m	5,5 m	7 m
-------	-------	-------	-------	-------	-------	-----

Illuminated Area

Sqm (5 lux minimum)	4000	1350	2000	2000	600	2400
---------------------	------	------	------	------	-----	------

Floodlights

Number, power & type	4x1000W Metal Halide	4x1000W Halogen	4x1500W Halogen	4x150W LED	4x1500W Halogen	4x150W LED
----------------------	----------------------	-----------------	-----------------	------------	-----------------	------------

Lamps Maintenance

Average hour life	2.000 hours	200 hours	200 hours	30.000 hours	200 hours	30.000 hours
-------------------	-------------	-----------	-----------	--------------	-----------	--------------



AMOG srl | I-80031 Brusciano (NA) | Tel. +39 081 658 8361 | sales@davinogroup.com

davinomixer.com